



Seal Tag



RFID TAGS WITH INTEGRATED FASTENERS PREVENT TAMPERING WITH THE CONTENTS OF SEALED CONTAINERS

- **Security** - RFID tags integrated into visually tamper-evident container seals
- **Adaptability** - Small and flexible to serve a wide range of applications
- **Easy application** - Attach quickly with integrated cable tie or wire loop
- **Clear evidence** - Visual recognition of seal status, with option of RFID reader detection of seal security or breach

HID Global® Seal Tag transponders are ideal for sealing commercial containers - bags, bins or boxes - to prevent unauthorized access to contents while in storage or during distribution. Seal Tag units integrate powerful RFID chips with high durability components, and secure, tamper-evident fasteners. Access to a sealed container's contents requires severing a tag's cable tie or wire loop - or breaching of the container itself - providing clear evidence of tampering.

vTamper tags

Each uniquely encoded Seal Tag vTamper RFID unit attaches anywhere a cable tie can be used, providing visual evidence when that seal is broken. Being waterproof, they have high resistance to aggressive liquids, UV rays, and temperature extremes. Thermoplastic elastomer (TPE) housings tolerate repeated bending or torsion. Bright colors provide excellent contrast for optical identification when laser engraved or embossed with logos, barcodes or text. Highly rugged on-metal options exist as well.

eTamper tags

Each Seal Tag eTamper NFC transponder becomes operational when its wire loop is securely closed or the disc sticker is applied. If the wire loop is broken, the tag is permanently unreadable, leaving evidence detectable both visually and via RFID. The printable coin form factor features the same eTamper functionality: The antenna breaks when the coin is removed - ideal for "proof of presence" applications or payment schemes.

eTamper tags may also be used as an "intelligent" seal for life safety device cabinets, including fire extinguishers, automated external defibrillators (AED) or other equipment that benefits from trusted maintenance.

edTamper tags

Seal Tag edTamper are tamper evident passive contactless RAIN UHF transponders allowing detection of their seal status via RFID. Visualizing the tag is not necessary to identify broken seals. The edTamper tags-provide a digital notification if a sealed tag has been compromised to quickly scan large sets of sealed items for integrity.

TECHNOLOGY HIGHLIGHTS:

- Integrated, secure fastening device
- HF 13.56 MHz version readable with ISO/IEC 15693 or ISO/IEC 14443A compatible devices incl. NFC and HID Trusted Tag® Services
- Broadband RAIN UHF version for worldwide use at 860 to 960 MHz
- Fully interoperable, standards compliant
- Visually, electrically and digitally tamper evident options
- Custom encoding or laser engraving on housing

APPLICATION AREAS:

- Asset tracking and logistics
 - Industrial bags, sacks and containers
 - Merchandise distribution and retailing
 - Life safety equipment maintenance,
- Returnable transport items
 - Reusable shipping vessels, cartons, bags, and canisters
- Waste management
 - Hazardous waste receptacles

SPECIFICATIONS



	Seal Tag					
	eTamper		vTamper			edTamper
	Coin	Teardrop	HF	UHF	UHF Mini	UHF
Base Model Number	7A1941-001 (DESFire) 7H0941-101 (TTS)	629960	729990-202	798990-202	7F2900	69899A-202 6E5961
ELECTRONIC						
Operating Frequency	13.56 MHz			860-960 MHz (Worldwide)		
Chip Type	MIFARE DESFire EV1 HID Trusted Tag (TTS)	ICODE SLiX		Higgs 3	Higgs 4	Higgs 3 UCODE G2iM+
Memory	4,096 bytes (DESFire) 8,096 bytes (TTS)	1024 bit EEPROM		512 bit user memory + 96 bit EPC + 64 bit TID	128 bit user memory + 128 bit EPC + 64 bit TID	512 bit user memory + 96 bit EPC + 64 bit TID 112 bit user memory + 256 bit EPC + 96 bit TID
Anti-Collision	Yes					
Reading Distance 2 W reader ERP, free space	N/A			Up to 26 ft (8 m)	Up to 32.8 ft (10 m)	Up to 16.4 ft (5 m) Up to 6.6 ft (2 m)
PHYSICAL						
Dimensions	1.5 x 1.5 x 0.3 in (39 x 39 x 8.5 mm)	Tag: 0.9 x 0.7 x 0.1 in (23 x 18 x 3 mm) Seal wire: 2.5 in (65 mm)	Tag: 3.3 x 1.0 x 0.1 in (85 x 25 x 3 mm) Cable tie: 15.0 x 0.3 x 0.1 in (380 x 6 x 2 mm)	Tag: 3.5 x 2.2 x 1.4 in (89 x 56 x 35 mm) Cable tie: 17.1 x 0.4 x 0.08 in (450 x 9 x 2 mm)	Tag: 2.4 x 0.5 x 0.08 in (60 x 12 x 2 mm) Cable tie: 7.8 x 0.1 x 0.05 in (200 x 2.5 x 1.2 mm)	Tag: 1.53 x 0.55 x 0.14 in (39 x 14 x 3.6 mm) Seal wire: 3.07 in (78 mm)
Mounting Method	Sticker	Integrated wire loop	Integrated cable tie			Integrated wire loop
Affixes To	Any material (hanging in free air)					
Housing Material	Polycarbonate		Tag: TPE / Cable tie: Nylon 6.6	Tag: High-impact plastic / Cable tie: Nylon 6.6	Tag: TPE / Cable tie: Nylon 6.6	PC/ABS
Color	Black (DESFire) White (TTS)	White	Tag: Yellow (Pantone 108) Cable tie: black	Black	Tag: White Cable tie: Black	White
Weight	0.18 oz (5.25 g)	0.04 oz (1 g)	0.42 oz (12 g)	2.33 oz (66 g)	0.08 oz (2.2 g)	0.07 oz (2 g)
CHEMICAL AND MECHANICAL RESISTANCE						
Water	IP65	IP68, 68° F (20° C), 6.6 ft (2 m) x 24 h				
Withstands Exposure To	Mineral oil, petroleum, salt mist, vegetable oil, HCL (10%), Bleach (5%); UV light					
Environmental Test Conditions	68° F (20° C), 100 h					
Flame Resistance						UL94V0 (self-extinguishing)
Vibration	IEC 68.2.6 [10 g, 10 to 2000 Hz, 3 axis, 2.5 h]					
Shock	IEC 68.2.29 (40 g, 18 ms, 6 axis, 2000 times)					
Impact			IEC 62262-IK06	IEC 62262-IK08	IEC 62262-IK06	
Axial / Radial Force	1000 N, 10 sec					500 N, 10 sec
Pull Resistance	> 150 N	> 10 N	> 550 N	> 780 N	> 65 N	> 10 N
Tag Bending	N/A		5.9 in (150 mm)	N/A	5.9 in (150 mm)	N/A
THERMAL						
Storage	-40° to +194° F (-40° to +90° C)		-40° to +158° F (-40° to +70° C)			
Operating	-13° to +158° F (-25° to +70° C)	-40° to +185° F (-40° to +85° C)	-40° to +158° F (-40° to +70° C)			
Shock / Fatigue	-40° to +194° F (-40° to +90° C) 100 x 5 min with 30 sec transition		-40° to +158° F (-40° to +70° C), 100 x 5 min with 30 sec transition			
OTHER						
Standards	ISO/IEC 14443A, NFC Forum Type 4	ISO/IEC 15693, 18000-3 Mode 1, NFC Forum Type 5		UHF EPC Class 1 Gen 2, ISO 18000-6C		
Options	Printed Logo, Encoding, Color	Encoding, laser engraving, alternate colors				
Box Size	1,000 pcs	300 pcs	1,000 pcs.	100 pcs	1,500 pcs.	800 pcs
Warranty	2 Years					



hidglobal.com

North America: +1 512 776 9000
Toll Free: 1 800 237 7769
Europe, Middle East, Africa: +44 1440 714 850
Asia Pacific: +852 3160 9800
Latin America: +52 55 5081 1650

© 2018 HID Global Corporation. All rights reserved. HID, the HID logo are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners.
2018-04-24-hid-rfid-il-seal-tag-ds-en PLT-01937

An ASSA ABLOY Group brand



ASSA ABLOY